



DT312PA Rugged Tablet

Slim, Rugged, Multi-Functional Wireless Computing

The DT312PA Rugged Tablet features the integration of high-brightness 11.6" touchscreen and a high-performance, energy-efficient Intel® Core™ Ultra processor within a slim, lightweight, durable package. With a built-in Wi-Fi module as well as optional front/ back cameras, smart card/CAC reader, barcode scanner and GNSS data capture modules, this robust tablet offers seamless information capture and transmission for improved workflow. Rated IP65, MIL-STD-810H/461G certified with a wide temperature range, the DT312PA Rugged Tablet provides reliable operation in harsh, mission-critical environments.



Features

- 11.6" sunlight-readable touchscreen, digital pen support
- Intel® Core™ Ultra 5/7 processor
- Microsoft® Windows® 11 IoT Enterprise operating system
- NIST compliant BIOS available
- Hot-swappable battery for 24/7 operation
- IP65-rated for water and dust resistance
- MIL-STD-810H for shock and vibration protection
- MIL-STD-461G for EMI and EMC tolerance
- Slim keyboard option for 2-in-1 applications
- QuickaccessSSD

Major Options

- 5 MP front camera and 13 MP back camera
- 2D barcode scanner (reads 1D and 2D)
- 4G LTE/5G
- Smart card/CAC reader
- GPS module

**** 4G/5G module, 2D scanner and GPS cannot be built onto same device.**

Specifications



Model	DT312PA	
System		
CPU	Intel® Core™ Ultra 5 processor 225U, 12 core (up to 4.80 GHz) Intel® Core™ Ultra 7 processor 255U, 12 core (up to 5.20 GHz)	
RAM	Ultra 5: 16GB LPDDR5 Ultra 7: 16GB to 32GB LPDDR5 * The memory is embedded. Alternative configurations are available by special order with MOQ.	
Storage	512GB to 2TB *Support quick access SSD function to easily replace the SSD without opening the back cover.	
Operating System	Microsoft® Windows® 11 IoT Enterprise	
NIST Compliance	NIST compliant BIOS available	
Display	11.6" LED-backlit, sunlight-readable 1000 nits touchscreen	
Display Resolution	1920 x 1080	
Buttons	1 x power button, 2 x brightness control buttons, 5 x programmable buttons	
Microphone	Built-in microphone with DSP for real-time video streaming	
Speaker	Built-in speaker	
Network Interface		
WLAN	Wi-Fi 802.11ax, 2.4/5/6 GHz three band	
BT	5.3	
I/O Ports		
USB Ports	1 x USB3.2 (Type-A), 1 x USB3.2 latest USB/charging	
DC-in Jack	1	Standard
Ethernet Port	1 x Ethernet 10/100/1000MB Base-T LAN	
24-pin Fischer Minimax Connector	1 x USB2.0, COM port, RJ45, power 5A (in), and power 2A (out)	Optional
Mechanical and Environmental		
AC/DC Adapter	Input: 100 to 240V AC; Output: 19V DC, 3.42A (65W)	
Enclosure	ABS + PC plastics and magnesium-aluminum alloy	
Battery Pack	43W Hot-swappable battery (11.4V, 3800mAh) (Optional) 60W Hot-swappable battery (11.4V, 5400mAh) (Optional) 90W Hot-swappable battery, (11.4V, 8000mAh)	
Dimensions (H x W x D)	8.3 x 12.4 x 0.78 in/212 x 316 x 20 mm	
Weight	3.43 lbs/1.55 kg	
Temperature	Operation*: -10°C to 60°C (14°F to 140°F) Storage: -50°C to 70°C (-58°F to 158°F)	
Humidity	0% to 90% non-condensing	
Certifications	CE, FCC Class B, IC, CB, RCM, IEC 60601-1, IEC62680, EPEAT, Energy star 8.0	
Durability	IP65, MIL-STD-810H and MIL-STD-461G certified	
Major Options		
Barcode Scanner	2D barcode scanner (reads 1D and 2D)	
Camera	5 MP front camera and 13 MP back camera	
GNSS Module	GPS	
Mobile Broadband	4G LTE/5G	

Accessories

The DT312PA Tablet has customized accessories to meet numerous deployment needs.

Digital Pen

Pen Tip	Diameter: 0.059 in/ 1.5mm, replaceable
Buttons	2 side buttons (right-click and eraser)
Battery	1 AAAA, replaceable
Color	Black
Dimensions	Length: 5.5 in/ 140 mm (including pen tip) Diameter: 0.38 in/ 9.7 mm
Weight	0.055 lbs/ 25 g



Slim Detachable Keyboard

Designed to connect to DT312PA tablet without switching and pairing



Battery Charging Kits



High Capacity Battery Pack

