

DT-810-FSR

Keyboard with Integrated Force Sensing Resistor

The DT-810-FSR from iKey(R) is a small-footprint industrial keyboard featuring an integrated Force Sensing Resistor pointing device. It is fully sealed in a stainless steel case to meet NEMA 4X specifications, which means it is resistant to grease, dirt, water and corrosive liquids commonly found in industrial environments. The DT-810-FSR has 81 keys, including 12 function keys.
Features:
12 Function Keys
81-Key Functionality
Fn Key for Secondary Legend Flexibility
Industrial Silicone Rubber Keypad
Integrated Force Sensing Resistor Pointing Device
USB and PS/2 configurations available
•
•

Product Code DT-810-FSR

CERTIFICATIONS	NEMA 4X, CE UL-60950, FCC Part 15 Class B
SHOCK	3 x 11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 10 feet straight (3 m) DESIGN: "Y" PS/2 Cable (providing separate keyboard and mouse connections), or single-cable USB
KEY SWITCH	MATERIAL: Industrial Silicone Rubber LIFE: Greater Than 10 Million Cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.05 oz +/- 1.06 oz (200g +/- 30g) FEEDBACK: Tactile with Mechanical Snap
VIBRATION	POWER SPECTRAL DENSITY: .04g/HZ FREQUENCY RANGE: 20Hz-2Khz DURATION OF TEST PER AXIS: 3 hours
POWER	PS2: KEYBOARD: 50mA@5V (from Keyboard port) POINTER: 35mA@5V (from Mouse port) USB: 85mA@5V (from CPU port)
COMPATABILITY	PS/2 KEYBOARD/POINTER: All Windows Operating Systems USB KEYBOARD/POINTER: All Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40C to +70C (-40F to +158F) OPERATING: -20C to +60C (-4F to +140F)
WEIGHT	3.75 lbs +/- 0.10 lbs (1.70 kg +/- 0.05 kg)
HUMIDITY	100% Humidity Resistant
DIMENSIONS	16.12" x 7.02" x 1.74" (w-h-d) 409.4mm x 178.3mm x 44.2mm
MODEL NUMBERS	DT-810-FSR-PS2: With PS/2 Cable DT-810-FSR-USB: With USB Cable