

DU-5K-TB

Keyboard with Integrated Trackball

The new DU-5K-TB by iKey features one of our most popular industrial keyboard layouts with an integrated, 25mm laser trackball. It is constructed with a highly rugged, ABS polycarbonate case and industrial silicone rubber keypad. The DU-5K-TB is completely sealed and designed to meet NEMA 4X specifications. The trackball pointing device is removable for convenient cleaning and has an adjustable tension ring. Keys above the trackball provide left, right and middle click functionality. The DU-5K-TB is also ADA 508 compliant.
Features:
Built-In Mounting Holes
Integrated Trackball
PS/2 or USB configurations available
Optional NVIS Compliant –Green B backlighting
•
•

Product Code DU-5K-TB

CERTIFICATIONS	NEMA 4X; UL 60950, IP65
SHOCK	3 x 11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 10 feet (3 meters)
KEY SWITCH	MATERIAL: Industrial Silicone Rubber LIFE: Greater Than 10 Million Cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 6.35 oz +/- 1.06 oz (180g +/- 30g) FEEDBACK: Tactile with Mechanical Snap
VIBRATION	POWER OF SPECTRAL DENSITY: .04g/HZ FREQUENCY RANGE: 20Hz-2Khz DURATION OF TEST PER AXIS: 3 hours
POWER	PS/2: KEYBOARD: 50mA@5V (from Kybd. port) POINTER: 45mA@5V (from Mouse port) USB: 95mA@5V (from CPU port)
COMPATIBILITY	PS/2 KEYBOARD/TRACKBALL: All Windows Operating Systems USB KEYBOARD/TRACKBALL: All Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40C to +85C (-40F to +185F) OPERATING: 0C to +65C (+32F to +149F)
WEIGHT	2.25 lbs +/- 0.10 lbs (1.02 kg +/- 0.05 kg)
WARRANTY	1 Year Limited
HUMIDITY	100%
DIMENSIONS	14.94" x 6.63" x 1.81" (w-h-d) 379.5 mm x 168.4 mm x 46.0 mm