Technical data

		MED9016	MED9019	MED9024
Display	Resolution	15.6“ TFT Full HD	18.5“ TFT Full HD	23.8“ TFT Full HD
	Brightness	450 Nits (typ.)	500 Nits (typ.)	250 Nits (typ.)
	Contrast ratio	800:1 (typ.)	1000:1 (typ.)	1000:1 (typ.)
	Displayable colors	max. 16.2 Mio.	max. 16.7 Mio.	max. 16.7 Mio.
Touch		PCAP multi-touch (glove-operated)		
Housing		Die-cast aluminum housing, powder coated		
Interfaces		1x HDMI 1x DisplayPort 3 x USB 2.0 1x USB slave 1x status LED in front[1]		
Optional interfaces		1x HDBaseT™ interface (transmitter)		
Power supply (integrated power supply)		24 V DC +/- 25 %		
Fixing		VESA100 sockets in back housing Optional: support arm adapter for mounting on the back housing		
Protection class		IP65 (front) IP65 (back side when using IP65 kit, which can be ordered separately, or when using the mounting arm adapter)		
Operating temperatur[2]		0 °C to +50 °C	0 °C to +50 °C	0 °C to +45 °C
Dimensions (W x H x D)		400 x 270 x 80 mm	465 x 310 x 80 mm	575 x 370 x 80 mm
Weight (without supplies)		approx. 5.0 kg	approx. 6.0 kg	approx. 8.0 kg

1 No Power button, device starts when voltage is applied

2 Without HDBaseT, with HDBaseT: TBD

Sistemi Avanzati Elettronici S.r.l.
Via Marconi, 11D - 13836 Cossato (BI)
+39 015 983206 | info@sisav.it | www.sisav.it