

Technical data

		MED9016	MED9019	MED9024
Display	Resolution	15.6" TFTFull HD	18.5" TFTFull HD	23.8" TFTFull HD
	Brightness	450 Nits (typ.)	500 Nits (typ.)	250 Nits (typ.)
	Contrast ratio	800:1(typ.)	1000:1(typ.)	1000:1(typ.)
	Displayable colors	max. 16.2Mio.	max. 16.7Mio.	max. 16.7Mio.
Touch	PCAPmulti-touch (glove-operated)			
Housing	Die-cast aluminum housing, powder coated			
Interfaces	1x HDMI 1x DisplayPort 3 x USB 2.0 1x USB slave 1x status LED in front ¹			
Optional interfaces	1x HDBaseT TM interface (transmitter)			
Power supply (integrated power supply)	24 VDC +/- 25 %			
Fixing	VESA100sockets in back housing Optional: support arm adapter for mounting on the back housing			
Protection class	IP65 (front) IP65 (back side when using IP65 kit, which can be ordered separately, or when using the mounting arm adapter)			
Operating temperatur ²	0 °Cto +50 °C	0 °Cto +50 °C	0 °Cto +45 °C	
Dimensions (W x H x D)	400 x 270 x 80 mm	465 x 310x 80 mm	575 x 370 x 80 mm	
Weight (without supplies)	approx. 5.0 kg	approx. 6.0 kg	approx. 8.0 kg	

¹ No Power button, device starts when voltage is applied

² Without HDBaseT, with HDBaseT: TBD