




Stainless steel display – SHD9000 series

The hygienic multi-touch monitor for clear display and ergonomic operation

The SHD9000 sets new standards to meet the highest demands of hygiene-sensitive environments and withstand the toughest conditions. Thanks to multi-touch, comfortable operation is guaranteed even with gloves. The industrial monitor is ideal for the food, beverage, pharmaceutical, and chemical industries. Compliant with EHEDG guidelines, DIN EN ISO 14159:2008, and certified cleanroom suitability by the Fraunhofer IPA Institute.



Everything at a glance

- > Maximum ergonomics due to tool-free adjustable rotation-tilt function of the tube adapter
- > Perfectly matched accessories (e.g. keyboard holder, VESA adapter)
- > Extended operating options with the additional key module
- > Easy installation thanks to hinged interface cover

Design meets hygiene

- > Fast and residue-free cleaning thanks to an outstanding design without screws and joints
- > Housing made of stainless steel (V4A), sturdy glass and high-quality silicone seals
- > Completely dustproof and protected against water ingress (IP69), alkali- and acid-resistant when using standard cleaning agents

Technology that inspires

- > Transmission of multimedia signals (image, touch operation) up to 100 meters over a single cable via integrated HDBaseT module.
- > Reliable multi-finger operation even with gloves thanks to advanced multi-touch technology.



Technical data

SHD9019		SHD9024
Display	Resolution	18,5" LED-Backlight 1920 x 1080 Pixel
		23,8" LED-Backlight 1920 x 1080 Pixel
Touch	PCAP multi-touch, tempered glass with shatter-proof film	
Housing	All-round closed stainless steel housing	
Cooling	Passive cooling, fanless	
Power supply	24 VDC (+/- 25%)	
Interfaces & Buttons	1x HDMI 1x DisplayPort 3 x USB 2.0 1x USB Slave 1x Status LED in Front ¹	
Optional connectivity	1x HDBaseT™ interface (receiver)	
Operating temperature	0°C to +50°C	0°C to +50°C
Dimensions (W x H x D)	468 x 313 x 77 mm	581 x 377 x 77 mm
Weight	Approx. 6,5 kg	Approx. 8 kg

¹ No ON/OFF button, the device starts when power is applied.

The content of this datasheet was created with utmost care. However, we shall not be held liable for the accuracy, completeness and topicality of any data and figures contained in this publication. The contents are subject to modifications and illustrations may vary. All product names are trademarks and registered trademarks, and as such are the property of the respective company owning trademark rights, in each case.

SHD9000 Serie Datasheet E 10-2025