Technical data

	SHP9019	SHP9024
Display Resolution	18,5“ LED-Backlight 1920 x 1080 Pixel	23,8“ LED-Backlight 1920 x 1080 Pixel
Touch	PCAP multi-touch, tempered glass with anti-shatter film	
Housing	All-round closed stainless steel housing	
Cooling	Passive cooling, fanless	
Processor	Intel® 13th Generation "Raptor Lake": U300E (5 core) or Core i5-1345UE (10 core)	
RAM	2 x RAM slot with up to 2 x 16GB DDR5	
Mass storage	2 x SSD slot with up to 2 x 256 GB m.2 SATA3 (one slot accessible by customer)	
Power supply	24 VDC or 230 VAC	
Interfaces & Buttons	4 x USB3.2 (10Gbit/s) Type A 3 x LAN dedicated 1x DisplayPort++ (2.1) 1x COM RS232 D-SUB 9 1x capacitive ON/OFF button on the front (can be deactivated via software)	
Optional connectivity	WLAN, Bluetooth, RFID, HDBaseT transmitter	
OS	Windows 11 IoT Enterprise LTSC 2024	
Other	Connection to ADS-TEC IoT platform Big-LinX via Software certificate	
Operating temperature	0°C to +50°C	0°C to +45°C
Dimensions (W x H x D)	468 x 313 x 77 mm	581x 377 x 77 mm
Weight	Approx. 6,5 kg	Approx. 8 kg

Sistemi Avanzati Elettronici S.r.l.
Via Marconi, 11D - 13836 Cossato (BI)
+39 015 983206 I info@sisav.it I www.sisav.it