iKey



SLK-101

Backlit Industrial Keyboard

iKey's SlimKey®SLK-101 keyboard provides full-sized versatility in a rugged, compact design. It features red LED backlit keys for use in areas with minimal lighting. Engineered for NEMA 4X protection from dust, water and corrosive liquids, the SlimKey®SLK-101 is ideal for use in industrial and material handling applications. The large numeric pad on the SLK-101 allows for easy data entry, while the robust polycarbonate case stands up in the roughest of conditions. Ask us about compatibility with Zebra product scanners and other devices.
Features:
10-Key Numeric Pad
12 Function Keys
Integrated Backlighting
MS Windows™Function Keys
Slim, Compact Design
USB and PS/2 configurations available
Optional NVIS Compliant –Green B backlighting (SLK- 101-461-NV) Mil Std 461G
•
•

Product Code SLK-101

CERTIFICATIONS	NEMA 4X UL60950, FCC Part 15 Class B
SHOCK	3x11 ms pulses of 50g on each of 3 axis
CABLE	LENGTH: 10' straight (3 m) DESIGN: "Y" PS/2 or USB Cable
KEY SWITCH	MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.05 oz. +/- 1.06 oz. (200g +/- 30g) FEEDBACK: Tactile with mechanical snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
POWER	PS/2: 210mA@5V (from Keyboard port) USB: 210mA@5V (from CPU port)
COMPATABILITY	PS/2: All Windows Operating Systems USB: All Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)
WEIGHT	1.5 lbs +/- 0.10 lbs (0.68 kg +/- 0.05 kg)
WARRANTY	1 Year Limited Warranty
HUMIDITY	100% Humidity Resistant
DIMENSIONS	14.60" x 5.55" x 0.92" (w-h-d) 370.8mm x 141mm x 23.4mm
MODEL NUMBERS	SLK-101-PS2: With PS/2 cable SLK-101-USB: With USB cable