

SLP-101

Full-Size Panel Mount Keyboard with Backlighting

iKey's SlimKey®SLP-101 panel mount keyboard provides full-size versatility in a rugged, compact design. It features red LED backlighting for low-light environments. When properly installed, the SlimKey®SLP-101 is engineered for NEMA 4X protection from dust, water and corrosive liquids. It is designed for easy integration into workstations, kiosks and industrial environments. The large numeric pad on the SLP-101 allows for easy data entry, while the robust polycarbonate case stands up in the roughest of conditions.

•
•

Product Code SLP-101

Certifications	NEMA 4X, CE UL 60950, FCC Part 15 Class B
Shock	3 X 11 ms pulses of 50g on each of 3 axes
Cable	LENGTH: 10' straight (3 m) DESIGN: "Y" PS/2 or USB Cable
Key Switch	MATERIAL: Industrial Silicone Rubber LIFE: Greater than 10 Million Cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.05 oz. +/- 1.06 oz. (200g +/- 30g) FEEDBACK: Tactile with Mechanical Snap
Vibration	Vibration POWER SPECTRAL DENSITY: .04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
Power	PS2: 210mA@5V (from Keyboard port) USB: 210mA@5V (from CPU port)
Compatibility	PS/2: All Windows Operating Systems USB: All Windows and Macintosh OS
Temperature Range	STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)
Weight	1.50 lbs +/- 0.10 lbs (0.68 kg +/- 0.05 kg)
Warranty	1 Year Limited Warranty
Humidity	100% Humidity Resistant
Dimensions	15.10" x 6.05" x 0.58" (w-h-d) 383.5mm x 153.7mm x 14.7mm SCREWS: 0.50" (12.7mm) CUTOUT: 13.70" x 4.65" (w-h) 348mm x 118.1mm
Model Number	SLP-101-PS2: With PS/2 cable SLP-101-USB: With USB cable